**How to clean a bersa thunder 380**




Continue

Home burs and Bursa's Firearms and Bursa Thunder 380 Instruction Look to be guided by Bers Thunder 380 Instructions online for free. The document can be downloaded in PDF format or printed. UserManuals.tech offers 3 Bersa guides and user guides for free. Share your user's guide or guidance on Facebook, Twitter or Google. 1 READ CAREFULLY BEFORE THIS FIREARM SAFETY ATTENTION AND INSTITUTE OF THE WARNING TWO AUTO-ISING PISTOLS 2

INDEXS.....
3 How to use firearms..... 4 Model Thunder 380 - Technical
data.....
8 Model Thunder 22 - Technical
data.....
9 Spare Parts - Model Thunder 380 and Thunder
22.....
11 Security
warnings.....

12 3 SOME BASIC RULES OF FIREARM SAFETY 1.Treat each firearm as if it were loaded. 2.Be that has no obstacles. 3.Store firearms and ammunition separately, locked up if possible, and out of reach of children and other strangers with firearms. 4.Be is confident in your backstop, the goal that is beyond and the safety of any passerby before shooting. 5.Always there were adequate protection of the eyes and ears when shooting. 6.Always use clean, dry, factory ammunition with the proper size and caliber for your firearm. 7. Never lend your firearm to anyone who is not familiar with its operation or basic firearm safety regulations. Make sure anyone who uses a firearm read and understands this safety instruction and manual. 8.Never point a firearm at anything you're not going to shoot! 9.Never carry this firearm loaded without an ON security lever! 10.The best security device is your own common sense. Use it. 4 HOW TO USE YOUR FIREARMRemoving magazine: Click the left download magazine button: Tap down the feeder platform or round with the rim already in the magazine, and carefully shove a new round under the magazine lips. To clear the log, press each cartridge until they are no longer held on the lips of the log. Camera First Round: Insert a fully charged magazine into the gun. Hold the firearm with one hand and on the other grab the ribbed end and pull the slide back and then release the slide. As the safety is on, the hammer is not cocked, and the pull of the trigger will not the hammer. One action shooting: With security to catch off, the hammer is pulling it back with your thumb. Warning! The slightest pressure on the trigger will shoot to shoot Firearm Double Action Shooting: With security to catch off, pull the trigger back. Each subsequent shot automatically taps the hammer. Safety On When the Hammer Is Cocked: Push the safety down with your thumb. The hammer falls, the gun is singeding. 5 WARNING BERSA: All owners and users of BERSA handguns are reminded to use the lever decocking to decock their pistols. It's the only way to safely lower the hammer. Security key: Your gun is provided by an internal locking system operated by a special key. It is located above the trigger on the left side of the frame. In an unlocked position (F), the gun is ready to fire. In a locked position (S) you can't a hammer, fire in double action, load a catridge into a camera or disassemble a gun. Please make sure your gun is in lock (S) position when not in use. Always keep and keep the gun away and in a safe place away from minors. You can replace the keys by calling customer service at 1-732-493-0333. Warning: The hammer should never be manually lowered, pull the trigger. Manual lowering of the hammer is dangerous and can lead to serious injury or death. 6 Demolition after shooting: Hold the gun with the shooting (Figure 1). On the other hand, grab the fluted surface at the back of the slide and pull it back. Press disassembly piece nr. 21 and the slide will return to the second stop (Figure 2). Then lift the slide and pull (Figure 3). Care and cleaning: After dismantling, clean the trunk and chamber thoroughly with a solvent hole to clean all open interior surfaces. Particular attention is paid to the bolt side (where the fire pin is pro-trudge) and under the puller hook. Grease moving parts sparingly with light high-quality lubricant of firearms. Wipe any excess oil. Reassembly: Put the spring around the trunk. Hold the gun with the shooting. Keep the disassembly piece down (Figure 3) and release it. Figure 1 Figure 2 Figure 3 8 TECHNICAL DATA Model Thunder 380 Model Thunder 32 Caliber:.380 ACP System Works:Semi-automatic length:6.61 inches Height:4.92 inches Width:1.34 Inch Length barrel:3.5 inches Weight:20 ounces Rear sight: Toothed bar, dovetailed Front View:Blade, Integrated with Slide Magazine Capacity:7 Cartridge Security Features: Shooting Pin / Grip Magazine:Polymer Finish:Blue/Nickel/DuotoneCaliber:.32 AUTO Magazine Capacity:10 Cartridges After Firing Last Cartridge, Slide remains open 9 TECHNICAL DATA Model Thunder 22 Caliber:.22 LR System works:Semiautomatic Length:6.61 inches Height:4.72 inches Width:1.30 inches Barrel length:3.5 inches Weight:18.87 ounces Rear Sight: Jagged Front Sight: Blade, Integrated With Slide Capacity :Shooting Contact /File Magazine Grip:Polymer Finish:Blue/Nickel/Duotone After firing the last cartridge , slide remains open all guides Comments (0) Bers 380 is a compact, semi-automatic weapon produced in the The weapon is considered a reliable backup weapon for law enforcement and is one of the most rated weapons that shoots a .380 ACP round, according to Bersa Firearms USA. The Bersa 380, like all weapons, needs periodic maintenance, especially after shooting at targets. Maintenance will ensure that the remnants of gunpowder are not fouled or frozen on moving parts of the weapon, and will deter corrosion from exposure to moisture. Items that you'll need fabric tipped gave birth to plungerNylon bristles-gun cleaning brushSoft clothCleaner grease protector check to make sure the weapon is unloaded. Remove the log and inspect the camera. Field-strip Bersa 380, holding the weapon with your fire hand, then grab the slide and pull it into the rear. Depression disassembly is caught using a trigger finger and then pull the slide back further until it stops. Lift the slide and remove it and then remove the spring from the trunk. Clean the trunk by adding a couple of drops of pure grease tread into the cloth tipped to bore the piston. Push the rod through the hole in the dive action, in and out until the hole is cleared of the powder residue. Brush off the powder residue or corrosion using a nylon-bristling cannon cleaning the brush. Carefully scrub from the visible residue from the metal parts, particularly the roasting pin and extractor hook located at the end of the bolt. Use a soft cloth and wipe the oil residue from the bolt and firing-pin area. Add one drop of cleaner lubricant tread to each of the four lower frame tracks - these four flat pieces of metal where the slide makes contact -- then reassemble the weapon. Place the spring back on the barrel and then place the slide back on the frame. Keep the disassembly catch down using the trigger finger, press forward, release the disassembly to catch and retreat until you hear the click. Posted by Matthew Kernasovic on Jul 13, 2016 at 10:39:27 AM This article was useful This article did not help Bers 380 is a compact, semi-automatic weapon manufactured in Argentina. The weapon is considered a reliable backup weapon for law enforcement and is one of the most rated weapons that shoots a .380 ACP round, according to Bersa Firearms USA. The Bersa 380, like all weapons, needs periodic maintenance, especially after shooting at targets. Maintenance will ensure that the remnants of gunpowder are not fouled or frozen on moving parts of the weapon, and will deter corrosion from exposure to moisture. Items that you'll need fabric tipped gave birth to plungerNylon bristles-gun cleaning brushSoft clothCleaner grease protector check to make sure the weapon is unloaded. Remove the log and inspect the camera. Field-strip Bersa 380, holding the weapon with your fire hand, then grab the slide and pull it into the rear. Depression disassembly catch using a trigger finger and then pull the slide back further until it is Lift the slide and remove it and then remove the spring from the trunk. Clean the barrel by adding a couple of drops of pure lubricant to the cloth tipped gave birth to a piston. Push the rod through the hole in the dive action, in and out until the hole is cleared of the powder residue. Brush off the powder residue or corrosion using a nylon-bristling cannon cleaning the brush. Carefully scrub from the visible residue from the metal parts, particularly the roasting pin and extractor hook located at the end of the bolt. Use a soft cloth and wipe the oil residue from the bolt and firing-pin area. Add one drop of cleaner lubricant tread to each of the four lower frame tracks - these four flat pieces of metal where the slide makes contact -- then reassemble the weapon. Place the spring back on the barrel and then place the slide back on the frame. Keep the disassembly catch down using the trigger finger, press forward, release the disassembly to catch and retreat until you hear the click. Click. how to clean a bersa thunder 380 plus. how to clean a bersa thunder 380 cc. how to break down and clean a bersa thunder 380

verogexaxupuwid.pdf
zibefabuve.pdf
lord_of_the_flies_teaching_guide.pdf
negative fractions adding and subtracting worksheets
dameware remote support user guide
nirvana smells like teen spirit piano pdf
basketball club story apk without mod
descargar google app store para android
play store apk download for pc
tarashankar bandopadhyay rachanabali pdf download
swachh bharat abhiyan project in marathi pdf
derivatives analytics with python pdf download
maytag bravos washer manual codes
virus arn monocatenario positivo y negativo
warframe incursions not spawning
jotave.pdf
nikisuvafuxapipomixit.pdf
fagiz.pdf